


ISSUE DATE: 3/2/2011

PROGRAM INFORMATION BULLETIN NO. P11-03

FROM: KEVIN G. STRICKLIN  
Administrator for  
Coal Mine Safety and Health



SUBJECT: Re-Issue P09-23 - Underground Scoop Accidents

**Scope**

Coal mine operators, miners and miners' representatives, and Mine Safety and Health Administration (MSHA) enforcement personnel should have this information.

**Purpose**

The purpose of this bulletin is to inform the mining community of best practices for reducing accidents related to the use of scoops and mobile equipment, where the equipment operators were struck by extraneous materials during operation.

**Information**

Examiners and mobile equipment operators should be alert to hazardous roadway conditions. Mine safety management systems and procedures should include methods for preventing, detecting, reporting, and correcting conditions or practices that expose scoop and other mobile equipment operators to these conditions. Examples of such hazardous roadway conditions include extraneous materials in the roadway such as belt structure parts, steel rails, loose roof bolts or partial bundles of roof bolts, steel pipe, and timbers. These conditions can be detected during applicable preshift, supplemental, or on-shift examinations of roadways, travelways, and track haulageways (refer to Sections 30 CFR §§ 75.360, 75.361 and § 75.362). Hazardous conditions found during such examinations must be corrected immediately or remain posted until corrected, pursuant to 30 CFR § 75.363. Following fatal accidents, MSHA has issued Notice to Provide Safeguard(s) pursuant to § 75.1403, requiring the operators at these mines to ensure that hazardous or extraneous materials are removed from travelways and haulageways where such equipment is to be operated.

The following best practices have been identified as having the potential to prevent accidents, injuries and fatalities to scoop operators:

Examine active roadways as often as necessary to ensure safety, particularly when hauling loose materials.

Maintain all roadways free of materials that may pose a hazard to equipment operators, passengers or other miners.

Emphasize safe operating procedures for equipment and maintenance of roadways in all training programs.

Ensure that suitable eye protection is worn whenever riding on or operating mobile equipment.

Ensure that adequate roadway clearance is available for mobile equipment, particularly with respect to vertical clearance from low overhead objects such as roof support or ventilation materials.

Keep loads contained within the confines of the scoop bucket.

Use only tested and approved mechanisms for pulling or towing.

### **Background**

Fatal coal mine accidents have occurred when operators of scoops or similar mobile equipment were struck and injured by extraneous material. Several fatalities and non fatal accidents were caused by loose debris thrown from the roadway by the scoop wheels or bucket. A significant percentage of the nonfatal accidents were eye injuries. Lack of clearance for the scoop car in the roadway and inadequate pulling or towing devices have been identified as contributing factors.

### **Authority**

The Federal Mine Safety and Health Act of 1977, Section 103(a).

### **Internet Availability**

This information bulletin may be viewed on the Internet by accessing MSHA's home page at [www.msha.gov](http://www.msha.gov) and then choosing "Compliance Info" and "Program Information Bulletins."

**Issuing Office and Contact Person**

Coal Mine Safety and Health

Terry Bentley, (202) 693-9521

E-mail: [bentley.terry@dol.gov](mailto:bentley.terry@dol.gov)

Coal Mine Safety and Health

Marcus Smith, (202) 693-9547

E-mail: [smith.marcus@dol.gov](mailto:smith.marcus@dol.gov)

**Distribution**

MSHA Program Policy Manual Holders

Miners' Representatives

All Mine Operators

Special Interest Groups